Attorney's Docket No. 1029650-000158 Application No. 10/509,657 Page 2

PLEASE ENTER

/Catherine Witczak/ (05/20/2008)

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

 (Currently Amended) An injection needle having a first ground facet formed on a distal end of a needle tube and at least two ground facets subsequently formed to provide a needle point, characterized in that

said first ground facet is of a substantially elliptical shape;

a plane which crosses said first ground facet perpendicularly thereto, [[and]] comprises a central axis of said needle tube, and is parallel to the central axis is regarded as a central plane;

the needle point is not present on said central plane; and said needle point is the only needle point.

wherein a planar surface forming said first ground facet forms an angle α with a central axis of said needle point, a planar surface forming said second ground facet forms an angle Φ with the central axis of said needle point, and a planar surface forming said third ground facet forms an angle θ with the central axis of said needle point, and wherein $\alpha \leq \Phi$, $\alpha \leq \theta$, and $\Phi \neq \theta$.

 (Original) An injection needle according to claim 1, wherein the minimum distance between said needle point and said central plane is in the range from 3 to 20% of the maximum outside diameter of said first ground facet in the direction of a minor axis thereof.

Attorney's Docket No. 1029650-000158 Application No. 10/509,657

Page 3

 (Currently Amended) An injection needle having an edge surface comprising three ground facets formed on a distal end of a needle tube to provide a

needle point, characterized in that

one of the ground facets which is remotest from said needle point is regarded as a first ground facet, and the other ground facets as a second ground facet and a

third ground facet;

said needle point is located on a boundary between said second ground facet

and said third ground facet;

an angle α between said first ground facet and a central axis of said needle

point, an angle $\boldsymbol{\Phi}$ between said second ground facet and the central axis of said

needle point, and an angle $\boldsymbol{\theta}$ between said third ground facet and the central axis of

said needle point are related to each other by: $\alpha < \Phi$, $\alpha < \theta$, and $\Phi \neq \theta$;

a plane which crosses said first ground facet perpendicularly thereto, is

parallel to the central axis, and comprises the central axis of said needle tube is

regarded as a central plane;

the minimum distance between said needle point and said central plane is in

the range from 3 to 20% of the maximum outside diameter of said edge surface in

the direction of a minor axis thereof; and

said needle point is the only needle point.

4. (Cancelled)

> Attorney's Docket No. 1029650-000158 Application No. 10/509,657

Page 4

5. (Previously Presented) An injection needle according to claim 3, wherein

the length of said second ground facet in the direction of the central axis and the length of said third ground facet in the direction of the central axis are in the range

from 20 to 80% of the whole length of the ground facets in the direction of the central

axis.

6. (Previously Presented) An injection needle according to claims 1.

wherein when the injection needle pierces a silicone rubber sheet having a thickness

of 0.5 mm at a penetration speed of 10 mm/mm., an initial value of the load with

respect to a penetration distance is 6 gf/mm or less.

7. (Previously Presented) An injection needle according to claim 3, wherein

when the injection needle pierces a silicone rubber sheet having a thickness of 0.5

mm at a penetration speed of 10 mm/mm., an initial value of the load with respect to

a penetration distance is 6 gf/mm or less.

8. (Cancelled)

9. (Currently Amended) An injection needle produced by a method

comprising grinding a distal end portion of a needle tube to form a first ground facet,

and grinding the first ground facet to form at least second and third ground facets

which provide a needle point, the injection needle is characterized in that

Attornev's Docket No. 1029650-000158

Application No. 10/509,657

Page 5

a plane which crosses said first ground facet perpendicularly thereto, [[and]] comprises a central axis of said needle tube, and is parallel to the central axis is regarded as a central plane:

the needle point is not present on said central plane; and said needle point is the only needle point.

wherein a planar surface forming said first ground facet forms an angle σ with a central axis of said needle point, a planar surface forming said second ground facet forms an angle Φ with the central axis of said needle point, and a planar surface forming said third ground facet forms an angle θ with the central axis of said needle point, and wherein $\sigma < \Phi$, $\sigma < \theta$, and $\Phi \neq \theta$.

- 10. (Previously Presented) An injection needle according to claim 9, wherein the minimum distance between said needle point and said central plane is in the range from 3 to 20% of the maximum outside diameter of said first ground facet in the direction of a minor axis thereof.
- 11. (Previously Presented) An injection needle according to claim 9, wherein when the injection needle pierces a silicone rubber sheet having a thickness of 0.5 mm at a penetration speed of 10 mm/min., an initial value of the load with respect to a penetration distance is 6 gf/mn or less.
 - 12. (Cancelled)

Attorney's Docket No. 1029650-000158

Application No. 10/509,657 Page 6

(Previously Presented) An injection needle according to claim 1.

wherein the substantially elliptical shape of the first ground facet possesses a major

axis, and said needle point is not present on said major axis.

14. (Previously Presented) An injection needle according to claim 1,

wherein the at least two ground facets comprise second and third ground facets

each possessing a curved outer edge, the central plane intersecting a distal end

region of the curved outer edge of one of the second and third ground facets.

(Previously Presented) An injection needle according to claim 3,

wherein said first ground facet is of a substantially elliptical shape possessing a

major axis, and said needle point is not present on said major axis.

16. (Currently Amended) An injection needle according to claim 3, wherein

the second and third ground facets each possess a curved outer edge, the central

plane intersecting a distal end region of the curved outer edge of one of the and

second and third ground facets.

17. (Previously Presented) An injection needle according to claim 9,

wherein said first ground facet is of a substantially elliptical shape possessing a

major axis, and said needle point is not present on said major axis.

18. (Currently Amended) An injection needle according to claim 9, wherein

the second and third ground facets each possess a curved outer edge, the central

10509657 - GAU: 3767

Attorney's Docket No. 1029650-000158

Application No. 10/509,657

Page

plane intersecting a distal end region of the curved outer edge of one of the and

second and third ground facets.

19. (New) An injection needle having a first ground facet formed on a distal

end of a needle tube and at least two ground facets subsequently formed to provide

a needle point, characterized in that

said first ground facet is of a substantially elliptical shape;

a plane which crosses said first ground facet perpendicularly thereto.

comprises a central axis of said needle tube, and is parallel to the central axis is

regarded as a central plane;

the needle point is not present on said central plane; and

said needle point is the only needle point,

wherein the at least two ground facets comprise second and third ground

facets each possessing a curved outer edge, the central plane intersecting a distal $% \left(1\right) =\left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left($

end region of the curved outer edge of one of the second and third ground facets.

20. (New) An injection needle produced by a method comprising grinding a

distal end portion of a needle tube to form a first ground facet, and grinding the first

ground facet to form at least second and third ground facets which provide a needle

point, the injection needle is characterized in that

a plane which crosses said first ground facet perpendicularly thereto,

comprises a central axis of said needle tube, and is parallel to the central axis is

regarded as a central plane;

the needle point is not present on said central plane; and

Attorney's Docket No. 1029650-000158 Application No. 10/509,657 Page 8

said needle point is the only needle point,

wherein the second and third ground facets each possess a curved outer edge, the central plane intersecting a distal end region of the curved outer edge of one of the second and third ground facets.